Certificate of Location of Government Corner

ID#: 540809 **Description:** SEC CEN 8 54 **Date Set:** 9/26/1997 **County:** Olmsted

Section: 08 **Township:** 105N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

PK nail

Reference Ties:

The corner falls 1' west of centerline of CSAH 8 and 23' north of centerline of twp road west
The monument is at the surface
This corner is lcoated by GPS measurement

Corner History:

8-26-1889 Thomas Fraser, County Surveyor, (Book A, Page 434, Survey No. 421) set stake and 3"x8"x28" stone at intersecting quarter lines. 1/16th South set 3"x8"x12" stone midway and on line at 19.94-1/2 chains (1316.37') to South 1/4.

4-24-1977 County Surveyor, 1/16th South, dug with backhoe in center of road and in line with fence. Found nothing.

2-20-1981 Thomas Taylor used computed center.

5-15-1987 McGhie & Betts, Inc. used computed center at intersecting quarter lines.

9-26-1997 GGG set pk nail at intersecting quarter lines.

5-23-1998 Ed Kuisle used computed center at intersecting quarter lines.

5-14-2001 Ed Kuisle used computed center at intersecting quarter lines.

4-5-2006 Vince Fangman found and used PK nail at intersecting quarter lines.

6-25-2007 County Survey Crew found pk nail at surface in good condition and measured its position using GPS.

10-18-2007 G-Cubed used computed center at intersecting quarter lines.

8-2-2018 Mark Severtson, County Surveyor, recommends using the computed intersection of quarter lines for the center of section. Based on the county's section breakdown, the pk nail, as located by GPS in 2007, falls 0.09' north of the computed center.