Certificate of Location of Government Corner

ID#: 540906 **Description:** 1/4 SEC COR 8 9 54 **Date Set:** 11/16/1982 **County:** Olmsted

Section: 09 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' north of fence west and in line with N-S fence
60d spike in NW side 24" Boxelder SW 15.78'
60d spike in NW side 12" Boxelder NNE 32.95'
Post w/sign 2' east
This corner is located by GPS reference stations "Edge A & B"

Corner History:

10-1853 Gov't Notes William B. Yerby, Deputy Surveyor North between sections 8 and 9. 40.00 chs. Set a quarter section post in mound of earth and sod. Deposited charcoal. Made trench and pits. Planted Osage Orange seed East and West.

5-6&7-1879 Thomas Hunter, County Surveyor, (Book A, Page 358, No. 349, and Old Fieldbook 5, Page 98) "1/4 post missing and no remains of it could be found, and no indication of where it stood was evident, and no one could be found who new anything about where it originally stood. So we established it on the line and midway between the section corners driving a stake marked 1/4S well into the ground for corner." He used the corner to set the 1/16 North, a temporary stake, midway (20.01 1/4 chs.) and on line to the NW Cor. 9, and the 1/16 South, a temporary stake, midway (20.01 1/4 chs.) and on line to the SW Cor. 9. He also set the 1/16 East, a stake, midway (20.02 1/2 chs.) and on line to the center 9, a stake marked 1/4S with mound and pits, set at intersecting 1/4 lines. He set the 1/16 East of the center 9, a stake, midway (19.97 1/2 chs.) and on line to the E 1/4 Cor. 9.

8-1889 Thomas Fraser, County Surveyor, (Book A, Page 434, No. 421) "Found stone 16x12x4 coming to point and underneath it found mark of old stake running down about two feet and quite plain. Put new stake by stone." He used the corner to set the Center 8, a "23x8x3 inch stone and post marked in grade of road", at intersecting 1/4 lines.

5-1896 Thomas Hunter, Deputy Surveyor, (Book A, Page 601, No. 546) "Found old stake as described by me in Survey No. 349 with stone by its side under old fence." He used the corner to set a temporary stake at the 1/16 North midway (20.01 1/2 chs.) and on line to the NW Cor. 9, and a temporary stake at the 1/16 South, midway (20.01 1/2 chs.) and on line to the SW Cor. 9 which he set by doubling the line and measure from the NW Cor. 9 over 1/4 Cor. 8-9. He set the 1/16 East, a stone boulder 22x10x8, midway (20.03 chs.) and on line to the Center 9, a stone boulder 22x8x6, set at intersecting 1/4 lines. He set the 1/16 East of the Center 9, a stone boulder 20x14x7, midway (19.96 1/2 chs.) and on line to the E 1/4 Cor. 9.

1957 McGhie's "Found limestone mon. between cor. Fe. Post. Set a 1" pipe over the stone. Stone is about 3' down and in line with fences running East and West and about 2' East of N-S fence." Chained 2645.9 East to a granite boulder found at the Center 9 and then 2635.7 East to a limestone and old sleigh shoe by new corner fence post at the E 1/4 Cor. 9. Chained 2643.3 South to iron grate found at the SW Cor. 9.

7-1972 County Surveyor (High Forest Fieldbook) "found stone and stake. Set a Cast Iron over stake." and (Card) "found recorded stone just SE of corner post in new N-S airport fence. Set CIM over stake with piece of oak post on East side just East of stone."

1981 Taylor Company measured the E-W 1/4 line of Section 8 and set a pipe at the 1/16 West of the Center 8.

10-7-1982 County Surveyor found the CIM completely out of the ground (apparently washed out) and leaning against corner post to new fence running West. Found spike in Willow--1972 R.P. Tie of 20.65 would come just on E side of the corner post. Dug here and found a 5 1/2"x11"x11" piece of limestone against the corner post. Removed stone but could not find stake.

11-16-1982 County Surveyor set a square pipe with a Cast Iron Cap at the intersection of the line from the W 1/4 Cor. 8 over Tayor's pipe at the 1/16 East and the tie of 20.65 from the spike in the Willow tree E'ly--1972 R.P. The corner came on the NE side of the corner post and at the location of the piece of limestone found 10-7-1982.

9-21-2004 County Surveyor found cast iron cap on telspar pipe down 0.5' in good condition. All old ties are gone.