Certificate of Location of Government Corner

ID#: 541104 **Description:** 1/4 SEC COR 11 14 54 **Date Set:** 11/20/2003 **County:** Olmsted

Section: 11 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls in centerline of E-W twp road and 4' east of centerline of twp road south
County highway disk in W side PP #9435 N 37.11'
Easterly of two anchor loops (center where the cable loops into the anchor) NE 53.45'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes Yerby 40.00 Set temp 1/4 sect. post West on true line between sects 11-14 40.30 Set a 1/4 sect. post in mound V7°57'E of earth & sod. Deposited charcoal made trench & pitts planted Osage Orange seed N & S

1874 T. Hunter (Bk. A pg. 242) reset a stake at the testimony of E. Judge.

1907 C. Armstrong (BK. B pg. 110) found nothing, set nothing.

1968 J. Kerr set nail in center road looking south and in line back north. Very little fence evidence north. - Meas. west in hopes finding clue to lost section corner. 10-11-14-15 - 1/16 fence south at sta. 1279.25 (R1338.5) in road cut - on continuing west tied up at CIM set on McGhies stake 2676.4 (R2677) (Hunter's meas.) will hunt again with tractor for corner at 10-11-14-15.

9-3-1971 County Surveyor found a large nail set by the County Highway Department

9-23-2003 V. Fangman found and used 1/2" iron as corner.

11-20-2003 County Surveyor found 1/2" iron rod down 0.4' in good condition. Set telspar pipe w/CIC from local ties over 1/2" iron rod down 0.4'.

10-15-2007 County Surveyor found cast iron cap on telspar pipe down 0.4' in good condition.