Certificate of Location of Government Corner

ID#: 541305 **Description:** SEC COR 13 14 23 24 54 **Date Set:** 3/31/2011 **County:** Olmsted

Section: 13 **Township:** 105N **Range:** 14W **Monument Description:** Cast iron Cap on Telspar Pipe

Reference Ties:

The monument is down 0.3'
Monument falls in line with fence east and 1/2' east of N-S fence
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes Yerby 80.00 set post - cor to sect 13-14-23-24 in mound of earth & sod. Deposited Charcoal. Made trench & pitts planted Osage Orange seed E & W of trench.

11-28-1975 County Surveyor dug 3'x3' NW of c. post to fence E (post on E side of N-S fence) Found nothing - not even old wire. Set CIM over 1/2" x 18" rod .85 E and .3'S of traverse nail and 1' NW of corner post. Left angle iron up 2' by CIM. Meas. N 1318 (ch) fence W, 1324 (ch) fence E, Meas. S 1313 (ch) fence s E and W - Corner not Final -

11-24-1978 County Surveyor decided more research is needed for this corner and removed CIM & iron reference point. Set spike in corner post East 1.65', and spike in fence post North 10.50'

2001 Rod Berg, Olmsted County Survey Department, computed a coordinate position of the 1975 location based on old traverse data.

3-31-2011 Joel Thoreson, County Surveyor, surveyed the computed coordinate position which falls at the intersection of a N-S fence and fence East. The fence posts have been replaced and the spikes in the fence posts from 11-24-1978 are gone. Check shots on the 16th fence corners north and south are very close to the distances shot on 11-28-1975. Set a 3' telspar pipe with cast iron cap at the computed coordinate location.