Certificate of Location of Government Corner

ID#: 541609 **Description:** SEC CEN 16 54 **Date Set:** **County:** Olmsted

Section: 16 **Township:** 105N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Computed center at intersecting quarter lines used by McGhie & Betts (2-16-1995)

Reference Ties:

This corner is located by GPS reference stations "Menshik A & B"

Corner History:

6-5-1872 T. Hunter No. 215 pg. 207 set a stone 4" by 5" by 12" at intersecting lines.

12-1957 K. McGhie set an iron an assumed point at the center of the road intersection and in line with the fence West.

7-20-1972 County Surveyor found a limestone 4" by 5" by 9". Set 1"x14" solid rod over stone and glass.

Note: This is a correction of a corner as set by K. McGhie. The correct corner (Hunter's limestone) lies 2.55' West and 3.0' South of the McGhie rod.

2-16-1995 McGhie & Betts found 1" rod to be .01' south and 0.98' west of computed center at intersecting quarter lines.

1-16-2001 McGhie & Betts used computed position at intersetion quarter lines.

4-1-2004 County Surveyor found 1" rod down 0.2' slightly leaning to the west.

7-12-2004 County Surveyor found 1" rod down 0.3' leaning west. Reset 1" rod from GPS and traverse data down 0.3'.

2-14-2006 McGhie & Betts used computed position at intersecting quarter lines.

10-15-2007 County Surveyor found 1" rod down 0.3' in good condition and removed.