Certificate of Location of Government Corner

ID#: 541805 **Description:** W SEC COR 18 19 54 **Date Set:** 10/5/1973 **County:** Olmsted

Section: 18 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.7'
The corner falls 15 1/2' south of centerline of TH 30 and in centerline of N-S twp road
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes John Ball, Deputy Surveyor North between sections 19 and 24. 80.00 chs. Set post and dug trench. Burr Oak 12 in. N74°W 530 lks. Burr Oak 11 in. N5 1/2°E 420 lks.

5-1874 Thomas Hunter (P. 245 No. 246), County Surveyor, found remains of old stake in the center of the road and set a boulder 8"x12"x15".

4-1878 Thomas Hunter (P. 335 No. 329) found stone.

10-1888 T. Hunter (P. 425 No. 414) found stone boulder.

9-1913 David Williams (P. 288 Book B), County Surveyor found hard head boulder as true undisputed corner. Minn. Hwy. Dept. assumed corner.

MHD const. Notes (30) Station 316+35.0 to centerline twp. road N & S. Making 2649.8 west to station at 1/4 13-24. Centerline Minn. 30 highway (highway align changed) very likely no corner found or searched for at all.

10-5-1973 County Surveyor found recorded boulder stone 5' deep and set a CIM over stone and thin iron tube.

10-1982 County Surveyor at 1/16th north dug from a point M & L to nail set in center of road and in line with fence for 4'+ East 2' + W, 3'S and 3'+ North. Clay down 6'. Good black dirt, but looked like previous wet area. Found nothing.

4-21-2004 County Surveyor found CIM down 0.7' in good condition.

9-5-2006 County Surveyor found CIM in good condition down 0.7'. Monument falls 1' west of centerline of road north and in centerline of road south.

4-25-2013 County survey crew found CIM in good condition,