Certificate of Location of Government Corner

ID#: 541806 **Description:** W 1/4 SEC COR 18 54 **Date Set:** 11/16/1982 **County:** Olmsted

Section: 18 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road and 3' north of fence west
County Survey Disk in top of CP WSW 47.17'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, John Ball, Deputy Surveyor, North between sections 13 & 18; 40.0 chs set post for 1/4 section corner. RPs- 11" burr oak N30°W 65 links, 11" burr oak N43°E 121 links

11-1857 E.P.Bircher, Surveyor, per J.B.Fellows, Deputy surveyed the road running north and south at this corner.

3-1858 J. Fellows Pg. 51 No. 74 meas. North 39.92 See survey for Sec. 13 - 10515

5-1874 T.Hunter, County Surveyor; found remains of old stake and NE BT stump. Set new stake.

9-1913 D. Williams P. 228 B did not set corner but on placing the SE corner S12 meas. 2 miles from NE 12 to SE 13 makes 2634' - 4 times which record of 2 x 19.92 = 2629.44 short 4.56'.

10-1973 County surveyor dug and found nothing.

10-1982 County Surveyor dug and found stub of old post.

11-16-1982 County Surveyor set a CIM over 1/2" rerod as corner. Note: To set the corner N-S we projected the main line of the fence from 600'± west out to the road and came 3' north of the fence corner on the west side of the road and 1' to 1 1/2' north of the corner post still standing on the east side of the road. Measure south 2631.46 to CIM over stone found at the W sec. Cor.18-19.

4-8-2004 County Surveyor found CIM down 0.6' in good condition.

6-25-2007 County Surveyor found CIM down 0.7' in good condition.