Certificate of Location of Government Corner

ID#: 541905 **Description:** W SEC COR 19 30 54 **Date Set:** 6/13/1974 **County:** Olmsted

Section: 19 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' north of centerline of twp road west and 2' west of centerline of N-S twp road
Bottle cap in SE side PP #7081 SW 77.64'
Center 20" Oak NW 69.5'
Center 20" smooth barked Oak SE 58.9'
Punched cross in N end 12" CMP SSE 64.55'
The corner is located by GPS measurement

Corner History:

4-1878 T. Hunter P. 335 No. 329 found remains of old stake in center road averred by James Farrel as driven by orig stake as it became rotted, meas. proved corner correct. Set stone boulder 5 x 8 x 18 in its place. - Meas. west 40.00 to stake well down. - Meas. north 39.89 to stone set in place old stake.

10-1888 T. Hunter p.425 No. 414 above stone gone - meas. from 1/4 cor. North E 1/4 24 south 39.90, - Meas. from 1/4 24-25 east 40.00, found stone set as 1/16 at 20.00 east from 1/4 24-25 105-15 (no mention of line projected east - (Set stake for corner as no stone at hand to set. - Meas. south 39.98 (2638.64') N 2-1/4°E to stake and stone set M & L. - 1/16 east meas. line carefully to 1/4 19-30 (a stake & stone set) 39.64 chs. short 16 lks. - set large pointed boulder stone at 19.72 (1301.52) chs. then 19.92 (1314.72) to 1/4 19-30 N88°W.

6-9-1971 County Surveyor dug with tractor carefully as expected only wood stake found stone very near 5 x 8 x 18 of 1878 Hunter with small L stones on N & S sides & wood stake on N side. 26" below road surface. west - 2' W centerline north (roads), - Pepsi cap on SE side PP #7081 SW 77.64, - center unmarked 20" oak NW 69.5, - center unmarked 14" pine northerly of 2 pines NE 96.0, - center unmarked 20" smooth barked oak SE 58.9, - punched cross in N end 12" driveway culv. SSE 64.55. Meas south to stone found at W 1/4 30 2635.7 (R2638.68) - 1/2 x 10" rod in yard on orig line now .12' N of line E 47.85.

6-13-1974 County Surveyor set CIM over stone.

Fall 1982 County Surveyor found monument in good condition.

6-25-2007 County Surveyor found CIM down 0.6' in good condition.