Certificate of Location of Government Corner

ID#: 541909 **Description:** SEC CEN 19 54 **Date Set:** 8/13/2008 **County:** Olmsted

Section: 19 **Township:** 105N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1/2" pipe

Reference Ties:

The corner falls in N-S fence row and in line with fence row west
Post w/sign 2' south
This corner is located by GPS measurement

Corner History:

10-9-1888 T. Hunter p. 425 no. 414 set stone as corner at inters of right lines - no size. - 16 west meas line carefully 39.04 short 43 links set stone on line stone at W 1/4 19 at 19.78-1/2 (1305.81) then 19.27-1/2 (1269.51) to W 1/4 cor for line south. N 88-1/2 W. - 16 south set stake M & L 20.11 (1327.26) N 1-1/2°E for line east. - 16 north set stone M & L 20.04 (1322.64) for line east, - 16 center NE 1/4 set stake M & L on E-W 1/16 line 19.97-1/2 (1318.35).

6-1968 J. Kerr High Forest Town board. Meas. 1/16 line thru center NE 1/4 19 on E-W 1/16 line in attempt to find stone in road - could not find stone at 1/16 corner north of center 19 - large wood post with boulders filled in around it well below surface as far as 2 feet in all directions. Accepted post as corner - no fence north of 1/16 at center of NE 1/4 19. Measure inconclusive.

10-4-1973 County Surveyor set 1/2"x2' iron on line and proportionate distance from west corner 19 over 1/16th corner stone found.

10-12-1982 County Surveyor, 1/16 north, dug from Huge C.P. south for 5' west 1 1/2' and east 2' by 2' to 2 1/2' deep to clay. Removed many boulders, some huge. Bits of rusty wire and nails to clay found nothing.

10-14-1982 County Surveyor, 1/16 west, dug from stone west 2 1/2 and north 2', found nothing.

10-19-1982 County Surveyor, 1/16 south, dug south and west from t.n. on south side of C.P. Found mark of old post 2 1/2' west and 2' south of the t.n. and then found mark of old stakes (approx 3" diameter and tapering to a point, down 1' and running 1' into clay.) 3.8 west and 3.3 south of the t.n. Left only spike in stake mark.
On line & meas from stone found at Center 24 (5-14-71) claimed ret M & L using cor fence post at 1/16 east 1325.5 (R 1326.27) - set offset N push line east - line indicates W 1/4 in line fence east 3.07 S.00 nail.

9-28-2007 County Surveyor found 1/2" rerod down 0.2' in good condition.

8-13-2008 V. Fangman set 1/2" pipe w/cap at intersecting quarter lines.

10-20-2010 County survey crew found 1/2" pipe with cap no. 14888 down 0.1' in good condition.