Certificate of Location of Government Corner

ID#: 542006 **Description:** 1/4 SEC COR 19 20 54 **Date Set:** 11/8/1982 **County:** Olmsted

Section: 20 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 3' west of centerline of N-S twp road and 5' south of old fence line west
Punch hole in S end CMP WNW 27.27'
County Survey Disk (up 4') in CP WNW 43.99'
Punch hole in N end CMP NW 34.04'
This corner is located by GPS measurement

Corner History:

1853 Govt Notes: Yerby 40.00 set a 1/4 sec post in mound of earth and sod. Deposited charcoal, made trench and pits, planted Osage Orange seeds E and W.

5-1870 R. Perry By T. Hunter Pg.177 No.188; Found stake.

10-1888 T. Hunter Pg.425 No.414; Corner gone. Set stake on sec. Line in line posts east.
1/4 post gone and as the road had been plowed and worked, no trace of it could be found, but several of the posts of the old fence running East as described in survey no. 188 at 3 in said survey are still standing, and said old fence being then in line of old corner, we fixed a temporary corner in line with said old fence, and in a direct line from G (Sec. Cor. 19-20-29-30) to A (Sec. Cor. 17-18-19-20)." He used the corner to set the 1/16 North, a stake and stone, midway (20.15 1/2 chs.) and on line to the NE Cor. 19. He set the 1/16 South, a stake, midway (20.24 chs.) and on line to the SE Cor. 19. He also used the corner to set the Center 19, a stone, at intersecting 1/4 lines, and then set the 1/16 West of the center 19, a stone, on line and at prorated Gov't measure (19.78 1/2 chs., then 19.23 1/2 chs. To the W. 1/4 Cor. 19) to the W 1/4 Cor. 19.

6-1968 John Kerr (Kerr Book 96, Page 76, and Kerr Book 98, Page 33, and Cards) measured from Sec. Cor. 19-20-29-30 North and found fence East at the 1/16 North at 1339 and fence East at 1/4 Cor. 19-20 at 2675 and fence West at the 1/16 North of 1/4 Cor. 19-20 at 3997.67. Dug at the 1/16 North of 1/4 Cor. 19-20 but did not find anything. He set an iron at 1/4 Cor. 19-20 on line and at Hunter's prorated measure from Sec. Cor. 19-20-29-30 to an iron set at the 1/16 North of 1/4 Cor. 19-20 in line with the fence West and at Hunter's measure East of the fence corner at the 1/16 North of the center 19 (Hunter measured the E-W 1/16 line of the NE 1/4 Sec. 19 in Survey No. 414).

1971 County Surveyor found the W 1/4 Cor. 19 and Hunter's stone at the 1/16 East of the W 1/4 Cor. 19.

10-25-1973 County Surveyor dug at the 1/16 South of 1/4 Cor. 19-20 from the line of the fence East (came 1339 North of Sec. Cor. 19-20-29-30) South to cover Hunter's 1888 and 1870 measures from Sec. Cor. 19-20-29-30. Found a boulder 6x8x20 dug into clay and in line with fence East (Stone 1338.46 North of Sec. Cor. 19-20-29-30 by 1982 measure) and nearly on line to Kerr's iron at Sec. Cor. 17-18-19-20.

10-26-1973 County Surveyor dug from 2670 to 2680 North of Sec. Cor. 19-20-29-30 and on the line from Sec. Cor. 19-20-29-30 over the stone found at the 1/16 North. Found only Kerr's iron. Projected line from the W 1/4 Cor. 19 over the stone found at the 1/16 East in 1971 and set point at Hunter's prorated measure at the Center 19. Point came appx. 1.6 East and 2.9 South of the corner post here but over a huge boulder--did not dig.

10-1-1982 County Surveyor found 1/2" rod that falls 5 1/2' south of corner post to fence west on west side of road and iron 4' west of centerline rock road. Took temporary ties, removed rod and dug 10' x7' x 4' hole. Did not find anything.

11-8-1982 County Surveyor set a Cast Iron Monument over the rod that falls as the corner at the intersection of the line from the W 1/4 Cor. 19 over Hunter's stone found at the 1/16 East and the line from Sec. Cor. 19-20-29-30 to Sec. Cor. 17-18-19-20 as set this survey (See Cert. Filed). The corner is .25 North and 1.66 East of Kerr's iron (removed).

5-4-2007 County survey crew found CIM down 0.5' in good condition.