Certificate of Location of Government Corner

ID#: 542105 **Description:** SEC COR 20 21 28 29 54 **Date Set:** 10/8/1982 **County:** Olmsted

Section: 21 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

Post w/sign 1' north
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William B. Yerby, Deputy Surveyor North between Sections 28 and 29. 80.00 chs. Set post corner to Sections 20,21,28,and 29. Br. Oak 8 in. N55°W 42 lks. Br. Oak 10 in. N61°E 117 lks. Br. Oak 5 in. S61°E 177 lks. Br. Oak 12 in. S7°W 521 lks.

5-10-1870 Robert Perry, County Surveyor, per T. Hunter, Deputy, (Book A, Page 177, No. 188) "Found stake standing." Measured 39.86 chs. West to center of sluice said to be built over corner at 1/4 Cor. 20-29, then 39.81 chs. West to Sec. Cor. 19-20-29-30. Measured 40.16 chs. North to stake found at 1/4 Cor. 20-21.

6-6&7-1892 Thomas Fraser, County Surveyor, (Book A, Page 491, No. 465) "Found stake standing as found in Survey 188." He used the corner to set 1/4 Cor. 28-29, a stone boulder, midway (39.92 1/2 chs.) and on line to Sec. Cor. 28-29-32-33. He also set a property corner 4.96 & 7/8 chs. East, an oak stake, and a property corner 9.93 & 6/8 chs. East of that, a stone boulder, both on line to 1/4 Cor. 21-28 24.84 & 3/4 chs. East of said boulder.

4-4&5-1896 William C. Fraser, County Surveyor, (Book A, Page 594, No. 540) "Found corner as given in Survey No. 465, Page 491." He used the corner to set the 1/16 North, a stone 16x4x3 inches, midway (20.12 1/2 chs.) and on line to 1/4 Cor. 20-21, a stone 22x6x3 inches, set midway (40.25 chs.) and on line to Sec. Cor. 16-17-20-21. He also set the 1/16 North of 1/4 Cor. 20-21, a stake, midway (20.12 1/2 chs.) and on line to Sec. Cor. 16-17-20-21. He set the 1/16 East, an iron stake, midway (19.82 1/2 chs.) and on line to 1/4 Cor. 21-28.

8-1903 Robert Fraser, Surveyor, (Old Fieldbook 10, Page 19 and 20) measured the North line of Section 29 at 79.65 1/2 chs. (no description of corner). Apparently set the 1/16 West.

7-1971 County Surveyor (High Forest Fieldbook and Card) measured West from 1/4 Cor. 21-28. Found iron pipe at 1312.95 and boulder with stake at 1640.13 (Thomas Fraser 1639.69). Dug at Thomas Fraser's property corner 9.93 & 6/8 chs. West of the boulder but could not find it. At 2623.96 West of 1/4 Cor. 21-28 found old cedar post. Dug around post but could not find stake. Set a 2" pipe as the 1/4 Cor. On the N.E. side of the cedar post on the line and at Thomas Fraser's prorated measure from 1/4 Cor. 21-28 over his boulder and stake found at his property corner. Reset the 1/16 East with a 1/2" rod .2 North and .97 East of pipe found to be midway (1312.0) and on line to 1/4 Cor. 21-28.

6-6-1975 County Surveyor found the pipe set 7-1971 and corner post now gone. Set a CIM over a 3/4"x12" iron as corner in E-W fence line at double the line and measure from 1/4 Cor. 21-28 over the 1/2" iron set at the 1/16 West in 1971.

6-6-1975 County Surveyor dug at the 1/16 North but could not find Will Fraser's stone.

7-8-1982 County Surveyor found and shot CIM. E-W fence now gone, only fence ridge remains. Set survey marker sign & post on north side of CIM.

7-8-2002 County Surveyor found CIM down 0.1' in good condition.