Certificate of Location of Government Corner

ID#: 542206 **Description:** 1/4 SEC COR 21 22 54 **Date Set:** 7/24/1972 **County:** Olmsted

Section: 22 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

Bolt in W side angle iron CP S 32.79'
Punch mark in N end CMP E 3.65'
Post w/sign 1' north
This corner is located by GPS reference stations "Pleasure A & B"

Corner History:

1853 Gov't Notes, Yerby; 40.0 set 1/4 section post in mound of earth & sod, charcoal, made trench with pits, and planted osage orange seeds NW & SE.

4-1896 W. Fraser BK A pg. 594. Found the original stake remains in the center of the road and set a stone in place of the stake.

1960 MHD found a small boulder and accepted it as the corner and set an iron riser. RPs- RPs- MHD disc corner fence post N 27.2, corner post steel S 30.0, MHD disc 30 " stump SW 55.3, NW corner old school SE 72.1.

6-1968 J. Kerr set a CIM over this riser.

7-24-1972 County Surveyor found recorded limestone 4x8x12. Reset CIM and 3/4" iron over stone with pump standard castings & old school desk pieces on all four sides. RPs- 32.79 S to large bolt on west side heavy angle, corner post holding steel brace of fence sputh which is 4' woven wire in heavy brush.

10-12-1988 County Surveyor found CIM leaning north. New RP- 3.65' east to punch mark in north end of CMP. Set sign & post 1.0' north of CIM.

Note: This is a correction of a corner from the MHD boulder and J. Kerr's CIM on 7-1972 the County Surveyor found the true corner as set by W. Fraser in 1896 2.8' North and 0.2' West of it's former location.

7-14-2004 County Surveyor found CIM at surface in good condition.