# Certificate of Location of Government Corner

**ID#:** 542306 **Description:** 1/4 SEC COR 22 23 54 **Date Set:** 3/31/1981 **County:** Olmsted

**Section:** 23 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Cap on telspar pipe

**Reference Ties:**

The corner falls 12' south of centerline of old road east, 4' west of fence north and 4' south of fence east
County Survey Disk in CP NE 6.05'
Post w/sign 2' north
This corner is located by GPS reference stations "Feltis F & G"

**Corner History:**

10-1853 Gov't Notes William B. Yerby, Deputy Surveyor North between sections 22 and 23. 40.00 chs. Set a quarter section post in mound of earth and sod, deposited charcoal, made trench and pits, planted Osage Orange seed NW & SE.

1890 The Chicago Great Western R.R. Right of Way Map shows the center of the R.R. tracks 598' West of the E 1/4 Cor. 22 (no description of corner).

7-1899 William Fraser, County Surveyor, (Book A, Pages 659-660, No. 587) "Could not find corner at this point." He measured 80.08 chs. From Section Corner 14-15-22-23 to Section Cor. 22-23-26-27 as set this survey.

3-31-1981 County Surveyor dug for this corner at a point midway (2643.95) between the section corners and 598' East of the center of the R.R. tracks but did not find anything. Set a telspar pipe with cast iron cap at this location. The corner came 12' South of the center of the old road East and 4' West of the fence North.

5-8-2007 County Surveyor found telspar pipe w/CIC at surface in good condition.