Certificate of Location of Government Corner

ID#: 542406 **Description:** 1/4 SEC COR 23 24 54 **Date Set:** 6/1/1974 **County:** Olmsted

Section: 24 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of CR 120 and in line with fence south
County Survey Disk in PP #45555 NE 31.23'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, Yerby; 40.0 set a 1/4 section post in mound of earth, charcoal, made trench with pits, and planted osage orange seeds E & W of trench.

1938 county highway department Bk.103 Pg.5; Found lower 12" of old stake. Set 1 1/4" pipe in hole.

1938 county highway department found boulder. Set 1 1/4" pipe riser and referenced to cottonwood south in fence line.

6-11-1968 J.Kerr set CIM over 1"x27" pipe in top of 1 1/4" pipe riser set by county highway department. RPs-corner lies in line fence north, bottle cap in black cresote corner post of fence west & north on east side of post 18" up N 40.8, bottle cap in tele pole SE side NE 30.45, bottle cap in tele pole N side ESE 139.1.

1974 County Surveyor set 10" CIM over (1968) CIM CDS in West side cor. Post North 48.9'. Bottle cap in PP #9544 NE 30.45 (gone).

4-23-1996 County Surveyor found CIM down 0.8' in good condition. CSD in West side cor. Post North 49.06'. CSD in PP #45555 NE 31.23'.

1-16-2002 County Surveyor found CIM down 0.8' in good condition.

10-15-2007 County Surveyor found CIM down 0.7' in good condition.