Certificate of Location of Government Corner

ID#: 542506 **Description:** 1/4 SEC COR 25 26 54 **Date Set:** 8/27/1971 **County:** Olmsted

Section: 25 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 5' north of centerline of E-W twp road and 1' west of fences north and south
16d nail in S side PP #15164 WNW 112.85'
Top center W end 24" CMP SW 40.1'
Punched cross in E end 24" CMP SSW 30.05'
Staple in ground wire in E side PP #15157 N 22.8'
This corner is located by GPS measurement

Corner History:

1853 Gov't notes, Yerby; 40.0 set 1/4 section post. RPs- 12" burr oak S23 E630 links, 10" burr oak S70 W 310 links.

1899 W. Fraser (BK. A pg. 659) found the stake remains which was declared as the true corner by P. Kelly and R. Starmer, pioneer settlers. Will then set a stone as the corner.

8-27-1971 County Surveyor set CIM over 5/8"x18" iron over original stone 6"x6"x16". RPs- 112.85 WNW to 16D nail in knot up 5' on S side PP #15164, 40.1 SW to top center end of 24" farm drive, 30.05 2.5'W of S to cross in E end 24" farm drive culv, 22.8 N to staple on ground wire in E side PP #15157, corner 5' N center E-W woods and 1' west of fences N & S.

1-23-2001 County Surveyor found CIM down 0.7' in good condition.