Certificate of Location of Government Corner

ID#: 542705 **Description:** SEC COR 27 28 33 34 54 **Date Set:** 10/25/1996 **County:** Olmsted

Section: 27 **Township:** 105N **Range:** 14W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 1/2' north of centerline of CSAH 35 and 18' east of centerline of Bear Cave Park entrance
Stewartville Sign NW 45.0'
PK Nail in W side PP NW 68.96'
Center 3 1/2" east gate post NE 49.57'
Center 3 1/2" west gate post NE 58.72'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes: W.B. Yerby, Deputy Surveyor North between Sections 33 and 34 80.00 chs. Set Section corner post Burr Oak 18 in. N35°W 350 lks. Burr Oak 18 in. S9°E 606 lks.

10-1904 Charles Armstrong P94 Bk B, county surveyor, found stone.

10-1905 Charles Armstron P96 Bk B found limestone.

1966 County Highway Department Book 321, set a 3/4" rod, by line and measure from the Quarter Corner of 27-34 over 1/16 west (rod gone in road reconstruction).

10-19-73 Roger Brand, county surveyor, dug and found Armstrong's limestone with a 1 1/2" x 18" iron shaft on the north side. Set the iron shaft as a riser and placed a cast iron monument over all. RPs- 59.02 NE to county highway department disc WNW side tele cable pole, 69.03 SE to county highway department disc WSW side pp# 10913, 40.7 SSEly to punch mark in top culv clamp lug E end, 46.18 Swly to same west end cracked lug, corner center road 1.76 E and .54 N to traverse nail.

3-5-92 Yaggy Colby Associates found a cast iron monument set by Roger Brand 10/19/73, 0.3' below bituminous surface.

7-1996 County Surveyor found CIM in good condition. Set reference pipe/cap in NE section 33 SW of corner.

10-25-1996 county highway department set 1" sq pipe/cap.

11-09-2001 County Surveyor found 1" square pipe w/cap at surface in good condition.