Certificate of Location of Government Corner

ID#: 542905 **Description:** SEC COR 29 30 31 32 54 **Date Set:** 6/11/1971 **County:** Olmsted

Section: 29 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in line with centerline of CSAH 8 east and 4' east of centerline of twp road north
County highway disk in PP #10813 NW 48.38'
Center punch mark in E end CMP SE 28.04'
Center punch mark in W end CMP SW 24.3'
NW corner of house foundation NE 132.42'
This corner is located by GPS measurement

Corner History:

1853 Gov't notes, Yerby; 80.0 set pot-corner to section 29-30-31-32. Made mound of earth & sod, deposited charcoal, made trench with pits, and planted osage orange seeds NW 7SE.

1884 T. Hunter (BK. A pg. 388) did not find the corner so he reset a stone by the gov't measures and records.

10-1888 T. Hunter Pg.425 No.414; Found corner

1892 Thos. Fraser (BK. A pg. 491) found the stone.

1915 J. Kerr (BK. B pg. 242) found the stone.

6-1968 J.Kerr drove 1/2" rod at county point called PI of curve or about 50' north of centerline blacktop on curve. RPs- Disc PP NW 46.47', disc in boxelder NE 51.0', corner lies west edge blacktop.

6-11-1971 County Surveyor set CIM. Corner comes 2.85' east and .18 north of county PI rod. RPs- 16D & disc on W side boxelder Nely 50.81', old county highway department disc on E side PP #C 10813 NW 48.4, punch mark on top lug east end road culv. SE 28.04, punch mark on top lug west end road culv. SW 24.3', NW corner house block foundation NE 132.42', external of road curve SSEly 51.0'.

11-09-2001 County Surveyor found CIM down 0.5' in good condition.

8-30-2004 WHKS Survey Crew found monument in good condition.

1-4-2005 County Surveyor found CIM down 0.5' in good condition.