Certificate of Location of Government Corner

ID#: 543504 **Description:** S 1/4 SEC COR 35 54 **Date Set:** 9/1/1971 **County:** Olmsted

Section: 35 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 5' south of E-W fence
Bottle cap in S side transmission PP W 168.8'
Pk nail w/brass disk in S side PP WNW 168.71'
Pk nail w/brass disk in S side PP W 409.69'
This corner is located by GPS measurement

Corner History:

1902 W. Fraser (BK. B pg. 16) drove a stake midway between the sec. Corners. On the S line of Section 35.

1910 C. Larson (BK. B pg. 144) found the stake.

1930 county highway department (BK. 57 pg. 40) found an iron drag tooth.

9-1-1971 County Surveyor dug and found drag tooth, set CIM over 1/2"x10" rod.RPs- 168.8 W to pepsi cap on S side trans. Pp, 132 ± E to center trans PP, 2.8 N to eyeball line south side PP E-W, 5.0 N to steel angle corner fence post about .7 east to post, 8'± W to eyeball line Nely of east row pp Nely.

1-30-2002 Yaggy Colby Associates survey crew found CIM down 6". Placed 5 ft. long fiber post on East side of monument.

6-11-2002 County Surveyor found CIM down 1' in good condition.