Certificate of Location of Government Corner

ID#: 543604 **Description:** S 1/4 SEC COR 36 54 **Date Set:** 5/31/2011 **County:** Olmsted

Section: 36 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Cap on Telspar Pipe

Reference Ties:

Post with sign 2.0' North
This corner is located by GPS reference stations "Bovine A & B"

Corner History:

6-1892 T. Fraser Pg.488 No.413; Found engraved township corner stone at the northeast corner of Section 1, T104, R14. Measured east 139.26 feet according to the tie from the original public land survey. Found remains of old stake in mound which agreed with gov't notes exactly which seems to be the only one in pan handle that does. Set a scoop shaped boulder stone 4"x10"x18"

5-1902 W. Fraser Pg.16B; Found boulder stone in center of mound. Measured west 139.26' to northeast corner of Section 1-104-14.

9-15-1971 County surveyor found engraved township corner at the NE corner of Section 1-104-14. Measured east 139' and found fair fence running north. Dug south of post, found several likely stones but angry bull attacked so had to abandon project. Never even filled hole.

6-12-1995 County Surveyor dug 139.26' east of the NE corner of Section 1-104-14 which was an engraved stone. Found broken corner fence post and many large boulders and limestone pieces but none that suitably matched the 4"x10"x18" stone as described by Fraser as a scoop shaped stone. The post stub is ± 3.1' south & ± 1.3' west of the traverse nail.

4-15-2011 Joel Thoreson, Olmsted County Surveyor, computed a location on the extension of a line from the SW corner of 36-105-14 through the NE corner of 1-104-14 and a distance of 139.26' east of the NE corner of 1-104-14.

5-31-2011 Olmsted County survey crew set 5' telspar pipe with cast iron cap at the location computed by County Surveyor on 4-15-2011.