# Certificate of Location of Government Corner

**ID#:** 550109 **Description:** SEC CEN 1 55 **Date Set:** 8/4/1959 **County:** Olmsted

**Section:** 01 **Township:** 105N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Mn/DNR Monument

**Reference Ties:**

The corner falls 33' north of E-W fence and under N-S fence
This corner is located by GPS reference stations "King A & B"

**Corner History:**

8-4-1959 Mn/DNR set iron pin as center.

4-29-1876 T. Hunter (P291 No.286) set stake flush with surface at inters lines. 6" Jack Oak West 71 1/2 lks. Set fencing line North and West to bluff line. Line North S. 15' W West S 88° 55' E.

10-28-1978 County Surveyor visited corner. Found corner post with fences East and South and fence North on the ground. Found a 16" Red Oak with protruding scar on E side which could possibly be Hunter's big tree. Set up the bearing distance and point came 3 1/2' West and 4 1/2' S of the corner post. We dug from this point North to the North side of the fence line but found nothing. Did not yet dig around corner post.

11-1-1978 County Surveyor center calculates 33' North in fence line fe 4' West and 3' South. Found nothing here. There is a pipe by a state of Mn. sign in the fe. North and 48.8 North of the t.n.

11-13-1981 Yaggy Associates used computed center at intersecting quarter lines.

5-17-1991 McGhie & Betts used computed center.

6-1-1992 McGhie & Betts set 1" pipe w/cap #11622 as center of section at intersecting quarter lines.

7-15-1994 McGhie & Betts used computed center.

3-22-2006 County Surveyor found pipe set by Mn/DNR.