Certificate of Location of Government Corner

ID#: 550305 **Description:** SEC COR 3 4 9 10 55 **Date Set:** 7/25/1966 **County:** Olmsted

Section: 03 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' west of centerline of twp road south and 3' south of centerline of CR 126
County highway disk in W side PP #6731 SW 47.8'
This corner is located by GPS measurement

Corner History:

1854 Set by Michael Karrick. 80.00 set post for corner to sections 3,4,9 & 10. Burr Oak 12 S 20 W 208. Burr Oak 10 N 60 W 128. Burr Oak 13 N 48 E 223. Burr Oak 13 S 32 E 269.

11-1857 John Fellows (Pg.42 No.64) show sec cor 1/16 cor East has BT's meas from 1/16 to 1/4 post 19.77 chs. (see survey for breakdown of sec 10)

6-1875 T. Hunter (P.280 No.277) found old stake on center road set new stake B.T.'s gone. 1/16 West set marked stake M & L 19.98 1/2. 1/16 center NE 1/4 9 set marked stake M & L 19.97 on N-S 1/16 line.

1939 County Highway Department found stone in center road.

7-25-1966 J. Kerr found nail in road with help of Forrest Wharton and Cat tractor also stone and hub below. Set CIM with 5/8" x 12" round steel rod below and half of original stone on West side, half on East side. Disc NE side cor. fence post SE 44.15. Disc (county) West side large power pole SW 47.8. Corner lies 2' West center road South (likely center now). Corner lies 2' West fence line North. 3/8" x 4' rod up 8" in fence line North under fence 100'.

9-12-1984 County Surveyor found CIM in good condition.

11-8-2002 County Surveyor found CIM down 1.2' in good condition.