Certificate of Location of Government Corner

ID#: 550404 **Description:** 1/4 SEC COR 4 9 55 **Date Set:** 6/25/1980 **County:** Olmsted

Section: 04 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 8' north of centerline of CR 126 and in line with fence north
RR spike in 18" Bur Oak N 29.52'
County Survey Disk in PP #6714 SW 74.12'
County Survey Disk in 7" Cedar NW 70.10'
This corner is located by GPS measurement

Corner History:

5-1854 Government Notes Michael Karrick, Deputy Surveyor West on true line between Sections 4 and 9. 40.00 chs. Set quarter section post. Bur Oak 15 in. N25°W 289 lks. Bur Oak 9 in. S40°E 61 lks. 80.00 chs. Section corner.

6-1875 Thomas Hunter, County Surveyor, (Book A, Page 280, No. 277 and Old Field Book 4, Pages 60-61) "Found stake as set by Freeman--Tested it by stump of S.E. B.T. and found It correct." He used the corner to set a stake at the 1/16 East midway (19.98 1/2 chs.) and on line to the N.E. Cor. 9, a stake at the 1/16 West midway (19.97 1/2 chs.) and on line to the center 9, and a stake at the 1/64 South midway (9.97 & 3/4 chs.) and on line to the 1/16 South.

6-24-1980 County Surveyor dug and found the remaining 4" of a 1 1/2" diameter stake in clay subsoil 3' deep in road. Drove a bolster pin (7/8"x10") in the stake hole. Measured 2637.15 East to Sec. Cor. 3-4-9-10, 2633.60 West to Sec. Cor. 4-5-8-9 and 657 1/2 South to the fence corner at the 1/64 South. This corner is 8' North of the center of the E-W road and in line with the fence North.

6-25-1980 County Surveyor set a C.I.M. over a 5/8"x14" rod over the bolster pin set 6-24-1980.

5-30-1985 County Surveyor found CIM in good condition.

4-8-2005 County Surveyor found CIM down 0.7' in good condition.