Certificate of Location of Government Corner

ID#: 550405 **Description:** SEC COR 4 5 8 9 55 **Date Set:** 8/18/1964 **County:** Olmsted

Section: 04 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls on E side of small stream
120d spike in 24" Cottonwood W 24.71'
County highway disk in TP SE 4.65'
Post w/sign 2' east
This corner is located by GPS reference stations "Rock Dell Highway Shop & 209"

Corner History:

5-1854 Michael Karrick 65.70 creek 6 lks wide runs NW. 74.70 same runs NE. 78.40 same runs NW. 80.00 set post for corner to sections 4,5,8 & 9. Burr Oak 11 N 65 W 215. Burr Oak 10 S 68 W 210. Dug trench.

6-1875 T. Hunter (P280 No.277) found stake set by surveyor Freeman. Tested by NW BT still standing and SW bT stump left as is. 1/16 East set stake M & L 19.97 1/2 set 1/64 South of above 1/16 stake at 10.01.

1922 county highway department creamery survey book 37 pg. 16 used something as corner. A limestone and pipe were used for many years as the corner.

8-18-1964 J. Kerr found Limestone. Set CIM over pipe. 120d in 24" cottonwood W 24.71. Disc in tele pole SE 4.65. 1" pipe up N .5. 3/4" pipe up S .5.

1984 County Surveyor found and used corner for R/W plat no. 37 for CR 3.

2-19-2003 County Surveyor found CIM down 0.2' in good condition.