Certificate of Location of Government Corner

ID#: 550705 **Description:** W SEC COR 7 18 55 **Date Set:** 6/14/1985 **County:** Olmsted

Section: 07 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road and 2' west of fences north and south
The monument is down 0.4'
County Survey Disk in SE side stub TP with TCM NE 37.08'
County Survey Disk in NE side PP #6542 SE 105.49'
This corner is located by GPS measurement

Corner History:

10-1853 John Ball 80.00 set post corner to sect. 7,12,13, and 18. Burr Oak 20 N 4 3°W 223 links. Burr Oak 15 N 31 1/2° E 163 links. No other tree near. Dug trench per instruction.

9-11-1984 Olmsted County Surveyor dug from t.n. (set in centerline rd and in line fences N & S) for 5 1/2' South, 3 1/2' East, and 5' West by 4' deep to clay. Conditions very poor on South side of road. Opened hole to dig North side of road and hit telephone cable but did not break it. Dug on SE'ly side of cable and hit 10" x 10" x 10" boulder down 2.4 beneath an old road. Removed boulder and found 4 1/2" diameter hole filled with wood pieces. Followed down 2 1/2' + to tappered point well down into clay (clay down 4'). Someone had dug around the stake well into clay, but had not dug clear to the end of the stake. Drove 1" square pipe in stake location (top down 4.8') and set boulder on E side of pipe. Corner .08 South and 1.95 W of the t.n. (removed) left nail at road surface over pipe.

6-14-1985 Olmsted County Surveyor set 20" CIM over 3/4" light pipe as the corner (from local RP's still in place) at location of stake and stone found in 1984. Corner in center of E-W road and 2' West of fence N & S. RP's: CSD in SE side post stub by telephone box NE 37.08. CSD in NE side PP #6542 SE 105.49.

9-18-2002 Olmsted County Survey Crew found CIM in good condition.

2-3-2010 Olmsted County Survey Crew found CIM down 0.4' in good condition.