Certificate of Location of Government Corner

ID#: 550904 **Description:** 1/4 SEC COR 9 16 55 **Date Set:** 6/14/1985 **County:** Olmsted

Section: 09 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 4' south of centerline of E-W twp road, 3' west of fence south and 2' west of fence north
County Survey Disk in E side CP NNE 37.88'
County Survey Disk in E side gate post NW 43.76'
This corner is located by GPS measurement

Corner History:

5-1854 Michael Karrick 5.20 creek 6 lks wide runs North. 40.00 set quarter section post. Burr Oak 8 N 9 E 101. Black Oak 12 S 45 E 160.

6-1875 T. Hunter (P.280 No.277) found short stake in center road avered by Peter Hogenson to be where orig. 1/4 stake stood, bearing trees grubbed and gone. 1/16 East set stake M & L 20.02 (S 89° W). 1/16 West set stake M & L 19.94 1/2 (S 88° 55' W).

7-1966 J. Kerr to find corner East for grading North. Drove 120d in center East West road in exact line of fence South, 41.8 from line of E-W fence on South side road. Meas East drove small nail in line fence South at 1/16 corner (record 1321.32) actural 1320.73 to fence line doubled distance but found stone at 1316.85 or 2637.58 from CIM SE 9 to 120d in line fence S at 1/4 9-16. This indicates 1/16 fence off some and recorded chainage different (land fairly level) or 1/4 cor should go West. (the section corner West should be replaced first (from West) over 1/16 stone on South side of SE 1/4 8 good chance it could be there.

9-20-1984 County Surveyor dug from t.n. (set in centerline road and in line with fence N) for 5' East, 3' South, and 4' West hole 1' North, 3 1/2' South, 3 1/2' East, and 4' West at the bottom by 6' deep to clay. Digging to corner line between the section corners & 1' North of line between section corners since Hunter shows 0°05' kink North at 1/4 cor. 9-16. Very good condition but no stake. Dug small hole to corner line and 2' North of line since Hunter shows 0°05' kink North here. Dug in line with N & S fence and W'ly to cover T.H. prorated location (2.31 W) Area on hilltop and cnt. Sand down 1' dug North to S edge hole dug in 1973. Dug from traverse nail South for 5' by 4 1/2' to clay. Old road 3 1/2' deep. Found top of stake by stone running down 1' well into clay. Stake 3.9 S. and .2W of traverse nail.

5-21-1985 County Surveyor dug on North side of previous hole. Found good stake with deep hole, down 4' drove RR spike in hole appx 5' North of stake found last year.

5-22-1985 County Surveyor dug from N edge previous dig, North for 4' + (in line with fence North). No old road, but at top if black dirt linee found about 4" of wood that could have been remains of old stake cut off during construction.

6-14-1985 County Surveyor set 20" CIM over 5/8" re-rod as corner on line between SW 9 (CIM) and SE 9 (CIM) and at T. Hunter's prorated measure between SW9 and SE9. Corner 4' S centerline E-W road, 3' West fence line South, and 2' West of fence line North. RP's C.S. Disc in E side C.P. NNE 37.88. C.S. Disc in E side gate post NW 43.76.

4-8-2005 County Surveyor found CIM down 0.1' in good condition.