Certificate of Location of Government Corner

ID#: 550909 **Description:** SEC CEN 9 55 **Date Set:** 5/25/2005 **County:** Olmsted

Section: 09 **Township:** 105N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
5/8" pipe w/cap RLS #41814

Reference Ties:

The pipe falls 1' south of E-W fence and 1.5' west of fence south.
This corner is located by GPS measurement.

Corner History:

6-12-1875 T. Hunter (P.280 No.277) set stake at true inters lines form 1/4 corners. 1/16 East set stake M & L 19.98 1/2. 1/16 North set stake M & L 19.95 1/2. 1/16 center NE 1/4 set M & L 19.97 on N-S 1/16 line. 1/16 West set stake M & L 19.98. Also set 1/64 stake between N 1/4 9 and 1/16 South M & L 9.97 3/4 (common land South of corner to 1/4 cor. or S line.)

9-26-1984 County Surveyor dug for T. Hunters stake at center 9. Dug from a point 1 1/2' North of the t.n. for 3 1/2' West, 2 1/2' East, and 6 1/2' N. A chokecherry tree on the West side of the c.p. kept us from digging there. Old c.p. stub on N. side present c.p. Line from t.n. at E 1/4 9 to W 1/4 9 at 2640 from SW 9 would come 2 1/2' N. of t.n. here. Line from t.n. at E 1/4 9 to a W 1/4 9 at full Hunter from 52 acre fe. would come 4 1/2 North of t.n. at center 9.

12-21-1990 V. Fangman used computed center.

5-25-2005 Massey Land Surveying set 5/8" pipe w/cap at intersecting quarter lines.

2-23-2010 County survey crew found 5/8" pipe with cap no. 41814 up 0.2' in good condition.