Certificate of Location of Government Corner

ID#: 551504 **Description:** 1/4 SEC COR 15 22 55 **Date Set:** 6/24/1993 **County:** Olmsted

Section: 15 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

the monument is down 0.1'
The corner falls 41 1/2' north of centerline of TH 30 and in line with fence north
Post w/sign 1' north
This corner is located by GPS measurement

Corner History:

5-1854 Gov't Notes: Michael Karrick 40.00 set quarter section post in mound with trench, pits, charred stake and osage orange seed NE and SW.

Minn Hwy Dept const notes: Station near curve 184 + 51.0 to fence line North making 2631.3 West to staion at 15-16-21-22. Station of PI 180 + 77.7 or 373.3 East to fence North centerline state 30 as built lies 45.6 South of section line as accepted by state. Found or likely centerline old twsp road. East to sec. cor. 2634.9 M.H.D. West to sec. cor. M.H.D.

6-24-1993 County Surveyor found trav. nail set previous survey. Set cast iron cap on telspar pipe as corner 41 1/2' North of centerline TH 30 and in line of fence North. Set sign and post 1' North of monument.

9-14-2006 County Surveyor found cast iron cap on telspar pipe at surface. Corner falls 1' south of sign & post.

4-26-2013 County survey crew found cast iron cap on Telspar pipe in good condition.