Certificate of Location of Government Corner

ID#: 551505 **Description:** SEC COR 15 16 21 22 55 **Date Set:** 9/14/2006 **County:** Olsmted

Section: 15 **Township:** 105N **Range:** 15W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The monument is down 0.5'
The corner falls 11 1/2' south of centerline of TH 30 and in centerline of N-S twp road
County Survey Disk in PP #53985 SW 102.92'
This corner is located by GPS measurement

Corner History:

5-1854 Michael Karrick 80.00 set post for corner to sections 15,16,21 and 22. Erected mound with trench, pits, and charred stake and osage orange seeds at each angle.

Minn Hwy Dept const. notes: Station 158 + 19.7 at centerline twsp road North and South making 2631.7 West to staion at 1/4 16-21 centerline state 30 as built lies. 11.3 North of section line as accepted or found or centerline old twsp road. Meas East to assumed 1/4 cor. 2631.4 M.H.D.

9-30-1991 County Surveyor set 1" square pipe w/cap at position used by state highway dept. in old survey used for R/W map. They used centerline of E-W rd and centerline rds South and North. This corner is now 11 1/2' South of centerline TH30 and in line of centerline South and mainline centerline North in 1980 when we set up this position the centerline TH30 was 12' North.

9-6-2006 County Surveyor found 1" square pipe w/cap loose, took local ties and removed.

9-14-2006 County Surveyor set 1" square pipe w/cap at surface from ties taken from pipe. CSD with concrete nail in PP #53985 SW 102.92'.

4-25-2013 County survey crew found 1" square pipe with cap at surface in good condition. Lowered pipe and cap 0.5' in preparation for 2013 road overlay.