Certificate of Location of Government Corner

ID#: 551706 **Description:** 1/4 SEC COR 17 18 55 **Date Set:** 8/17/1964 **County:** Olmsted

Section: 17 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' west of centerline of N-S twp road and in line with fence west

Corner History:

5-1854 Michael Karrick 38.00 enter barrons SW. 40.00 set quarter section post. Bur Oak 9 S 80 E 180. Dug trench. 50.00 enter uncultivated marsh beares NE. 70.00 leave same bears NE.

6-1895 W. Fraser (P.579 No.529) corner could not be found, located M & L 39.95 set boulder 8" x 10" x 30". 1/16 North set stake M & L 19.97 1/2.

8-1964 J. Kerr local survey S.18 found stone placed 1/2" x 14" square steel rod after pushing large boulder West into hole dug in searching for stone. Corner lies a little West of center line of road N & S. Disc power pole WSW 22.3. Disc fence post E 37.45. Cross in North end drivewal culv extended. Corner in line of fence running West (electronic meas N 2635.5 set 17-18-19-20 by records M & L) 1317.65 x 2 = 2635.30 (record 1318.45). RP's + in West end large culv. NW 26.13. + in East end large culv. NE 27.0.

10-16-1973 County Surveyor found and used monument in setting section corner to south.

8-8-1984 County Surveyor found CIM in good condition.

4-20-2009 County Surveyor found CIM down 0.9' in good condition.