Certificate of Location of Government Corner

ID#: 551804 **Description:** 1/4 SEC COR 18 19 55 **Date Set:** 2/12/2009 **County:** Olmsted

Section: 18 **Township:** 105N **Range:** 15W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The monument is down 0.4'
The corner falls 30' south of centerline of TH 30 and 3' west of centerline of CR 149
County highway disk in W side PP #6591 SE 57.61'
County highway disk in W side PP #6592 SW 55.75'
This corner is located by GPS measurement

Corner History:

5-1854 Michael Karrick 39.85 set quarter section post in mound with trench, pits, charred stake and Osage Orange seeds NE and SW.

6-1895 W. Fraser Pg.581 No.530 found stake in centerline of road, set stone as corner.

6-1895 W. Fraser Pg.582 No.531 found corner above.

Mn/DOT Constr. Notes - took centerline road south and centerline state road 30' north of old road centerline.

6-10-1993 County Surveyor decided to use the 1/4 line in sec. 18 and 30' south of centerline TH 30 for corner location.

9-6-2006 County Surveyor set Pt. "Hinder" and used saturation Pt. "Johnson" to establish a final location.

2-12-2009 County Surveyor set 1" square pipe w/cap at surface from computed coordinates.

4-25-2013 County survey crew found 1" square pipe with cap at surface in good condition. Lowered pipe and cap 0.4' in preparation for 2013 road overlay.