Certificate of Location of Government Corner

ID#: 551805 **Description:** W SEC COR 18 19 55 **Date Set:** 6/11/2009 **County:** Olmsted

Section: 18 **Township:** 105N **Range:** 15W **Monument Description:** 1" square pipe w/cap RLS #42638

Reference Ties:

The monument is down 0.5'
The corner falls 5' south of centerline of TH 30 and 1' west of centerline of field drive south
The monument is at the surface
This corner is located by GPS measurement

Corner History:

10-1853 John Ball 80.00 Set section post corner to sec. 13, 18, 19 & 24. Burr Oak 10" N 31º W 780 lks. Burr Oak 10" S 89º W 380 lks, dug trench.

6-1895 W. Fraser (P.581 No.530) found boulder placed by Rairson. Set stake with boulder by side.

Minn State Highway constr notes. Took centerline road South, placed centerline state road 30' North of old road centerline station (26 + 36.1) record 2632.4.

9-6-2006 Olmsted County Survey Crew found aluminum/metal disc set in 5" square concrete sleeve down 0.5' in good condition. Set control to determine validity of location of monument.

6-4-2009 Olmsted County Survey Crew found concrete cylinder with disc down 0.9' in good condition, took local ties and removed.

6-11-2009 Olmsted County Survey Crew set 1" square pipe w/cap at the location of the concrete cylinder with disc.

2-3-2010 Olmsted County Survey Crew found 1" square pipe w/cap at surface in good condition.

4-25-2013 County survey crew found 1" square pipe with cap at surface in good condition. Lowered pipe and cap 0.5' in preparation for 2013 road overlay.