Certificate of Location of Government Corner

ID#: 551809 **Description:** SEC CEN 18 55 **Date Set:** 8/31/1984 **County:** Olmsted

Section: 18 **Township:** 105N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1/2" re-rod

Reference Ties:

The monument is down 0.3'
The corner falls under E-W fence and 1' east of wood fence post
Post with sign is south 2'
This corner is located by GPS measurement

Corner History:

6-20-1895 W. Fraser (P.581 No.530) drove stake at true intersecting lines. West set boulder stone for line South at 10 chs. East set boulder stone for line South at 10.01 1/4 chs. 1/16 East set stake M & L 20.02 1/2. Bearing N-S 1/4 line S 35' W. Bearing E-W 1/4 line. N 88V 40' W.

8-28-1984 County Surveyor 1/64th East: Found W. Frasers stone, a 2' long boulder with 10" x 7" bottom and 4" x 6" top with and 1 1/4" drill hole on top standing against the South side of old post. There was also a wood stake on the West side of the stone. Stone .67 South and .42 East of the t.n.

8-28-1984 County Surveyor 1/64th West: Found W. Frasers stone, a 16" long pyramid shaped boulder, with dome top 6" x 7" and 1 1/4 drill hole on top down 2" in pasture. Stone 6' North of E-W fence and 15 1/2' West of the fence South, and 5.3 North and 20.8 West of the t.n. (eyeball). Set a 5/8" rod on the N side of the stone.

8-31-1984 County Surveyor found W. Frasers stake standing under the E-W fence-8" still sticking out of the ground!! Stake 3" diameter and 33" long and sharpened to a long point. Removed stake to office and set a 1/2" re-rod in its place. Iron .9 East of wood fence post in E-W fence line.

3-30-2001 V. Fangman used computed center at intersecting quarter lines.

10-13-2010 County survey crew found 1/2" rod in good condition