# Certificate of Location of Government Corner

**ID#:** 551906 **Description:** W 1/4 SEC COR 19 55 **Date Set:** 7/28/2010 **County:** Olmsted

**Section:** 19 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Cap on Telspar Pipe

**Reference Ties:**

Corner falls 70' east of center of overhead electric transmission line.
Post with sign east 2'

**Corner History:**

10-1853 John Ball 40.00 set post and drove charred stake for quarter sec. cor. Built mound with trench per instructions. Planted SE Osage Orange NE Apple.

1981 Township Survey Data Map shows WHKS Company set nail in fence line and measured 2636.83 to the southwest corner of section 19 and measured 2646.45 feet to the northwest corner of section 19.

7-28-2010 Olmsted County Surveyor and crew visited the area of the corner. Measured the west line of section 19 at a distance of 5279.09 compared to the 1981 WHKS measurement of 5282.28. It was assumed this difference is due to a new monument location at the northwest corner of section 19. Therefore, we computed a position on line between the section corners and 2636.83 feet north of the southwest corner of section 19. Found large nail, possibly from WHKS, laying flat near the computed position. Fences are gone but the computed position fit the field divisions north, south, east and west. Set a 5' telspar pipe with cast iron cap at the computed location.