Certificate of Location of Government Corner

ID#: 552005 **Description:** SEC COR 19 20 29 30 55 **Date Set:** 8/9/1965 **County:** Olmsted

Section: 20 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' west of centerline of twp road south and 1' south of centerline of E-W twp road

Corner History:

5-1854 Michael Karrick 80.00 set post for corner to sections 19,20, 29 and 30. Erected mound with trench, pits, charred stake and Osage Orange seeds at each angle.

9-1876 T. Hunter (P.304 No.299) found corner gone completely. No knowledge of corner. Meas N 1/4 29 to NW cor. 30 119.77 chs over ran 7 links. Meas SW 29 to W 1/4 20 119.94 chs short 6 links. Set burr oak stake with stones around its bottom as corner. Meas South 39.98 to stake set M & L (2638.68). Meas North to 1/4 19-20 39.98 stone found (see 1/2 20-29 H.S. Gillman for 1/16 North). Meas East 40.00. Meas West 40.03 1/2.

6-1895 W. Fraser (P.582 No.532) found corner set P.304. Set new stake with limestone by its side. West 1/4 cor. gone set stakes at 1/16 East with 1/64 stake set between a stone 1/16 and corner. (SE 19) also set S 1/4 19.

8-9-1965 J. Kerr relocated from previous survey notes. Set CIM over 1/2"x3' rod.

9-3-1992 County Surveyor found CIM in good condition deep in road.

9-8-2006 County Surveyor found CIM in good condition down 1.1'. Monument falls 1' south of centerline of E-W road and 1' west of road south. Disc in PP to the SE ok. Did not check. Tie to the SW and telephone control post to the NW gone.