# Certificate of Location of Government Corner

**ID#:** 552309 **Description:** SEC CEN 23 55 **Date Set:** **County:** Olmsted

**Section:** 23 **Township:** 105N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

**Reference Ties:**

**Corner History:**

4-11-1878 T. Hunter (P.334 No.328) set stone 4 x 10 x 20 at true transit inters lines. 1/16 West set stake 19.88 1/2 M & L N 89° W. 1/16 East set stake 19.97 M & L N 89° W. 1/16 South set stake 20.03 1/2 M & L N 1 1/4° E. 1/16 center SW 1/4 23 set stake inters lines.

8-1963 J. Kerr meas line from North at state notes corner. Meas 2645 to E-W fence at center. Dug some from center stone no probes, not conclusive.

7-20-1971 County Surveyor measured from center road at 1/4 23-24 (stone 2.35' East) 1/16 fence South at 1319.65 corrected (R1318). 1/4 line fence North at 2636.98 corrected iron set to stone found East (R2636). Meas from stone at 1/4 22-23 East 2624± (R2624.82). Set bottom part of steel fence post as corner at meas above little South of corner post of fences E-W-N but lines with main line fences. Ran direct aerial 28.5 offset South iron within .2' could be N radios antenna broke so 28.5 South set up within the .2'. No references to corner, could not find 4 x 10 x 20 recorded unless some of numerous stones in area were part of stone. No limestone found. Corner accepted S 1/4 found, N 1/4 assumed. So no N-S 1/4 line run thru heavy crop land, not needed.