Certificate of Location of Government Corner

ID#: 552804 **Description:** 1/4 SEC COR 28 33 55 **Date Set:** 7/2/2002 **County:** Olmsted

Section: 28 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls in line of fence rows north and east
Post w/sign 1 1/2' south
This corner is located by GPS measurement

Corner History:

5-1854 Gov't Notes: Michael Karrick 40.00 set quarter section post in mound with trench, pits, charred stake and Osage Orange seeds NE and SW.

6-1875 T. Hunter (P.283 No.280) found fence post set in middle of mound set by A. Peters by side of old gov't 1/4 post. 1/16th West set marked stake M & L 20.00 chains (S 89° 15' W). East set stake at 22.40 chains or 2.50 chains East of 1/16 corner (no described) then 17.40) (chains to boulder) 23 x 8 x 6/2 set on testimony of adjourining land owners total 1/2 mile 39.80 2626.4 with midway 1313.4. 16th South set stake M & L 20.02 to center 33 bearing West S 89° 15' W East N 89° 10' E South N 10' W.

7-1893 W. Fraser (P.521 No.487) found mound with remains of old post in center of mound left as found. 1/16th W found remains of old stake set by Hunter (P.283) which proved to be M & L 19.98 1/2 1319' set stone 18 x 7 x 2 likely in place of old stake. NW corner 33 found Hunters stake set stone 2 x 9 x 18. W. Fraser (P.523 No.488 S.28) Frank Roeder, Peter Lee, Bottel Magneson used corner and 1/16th corner West as (P.521) used to set limestone at center 28.

12-23-1971 County Surveyor Meas East from nail set in center blacktop in 7-29-1971, found exact size limestone 2 x 7 x 18 3' North and 2' East of fences running East and South. Meas about 1318.8 ± (R1319).

7-2-2002 County Surveyor dug hole 4' x 4' x 3' to cover line and double distance from SW 28 over 1/16th West (found stone). Found old corner post stub at position. Set 6' long telspar w/Cast Iron Cap at double distance and on line.

5-6-2003 County Surveyor found telspar with CIC up 0.2' in good condition.