Certificate of Location of Government Corner

ID#: 552809 **Description:** SEC CEN 28 55 **Date Set:** **County:** Olmsted

Section: 28 **Township:** 105N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

This corner is located by GPS reference stations "Kolstad A & B"

Corner History:

7-7-1893 W. Fraser (P.523 No.488) set stone 2 x 7 x 22 at true inters of right lines.

8-9-1971 County Surveyor ran random aerial from center blacktop at 1/4 28-29 a nail set 5277' North of co. HD CIM set at 1/4 32-33 somewhere near conflicting records. Found badly shattered limestone 2 x 7 x 19 on West side of corner post of fences South and East. Replaced pieces of limestone with good sized sapling with slim boulders on 2 sides of sapling. Line fell 7.4' South of corner found, con't line East on 64' North this line corrected to true line fell 2.6' South of .00 point set in line fences East and West proving center stone as found to be correct and as 1/4 27.28 could not be found and 1/4 28-29 a stone 6 x 6 x 30 set M & L 2635.38 by W. Fraser and found again by Hunter in 5-1896 now in very deep fill (10' ±) it would seem 1/4 28-29 would have to be reset by line and meas from West (P.598) Hunter creating necessity of reproducing center 29 from West then pushing line East and setting 1/4 28-29.

4-30-2003 County Surveyor set 60d spike and assumed location of center and set 2 points to GPS and determine location.