Certificate of Location of Government Corner

ID#: 552904 **Description:** 1/4 SEC COR 29 32 55 **Date Set:** 10-22-2012 **County:** Olmsted

Section: 29 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Cap on Telspar Pipe

Reference Ties:

The monument is up 0.3'
The corner falls in the N-S fenceline
This corner is located by GPS measurement
Post with sign 2.2' north.

Corner History:

5-1854 M. Karrick 40.00 set quarter section post in mound with pits, charred stake.

6-1875 T. Hunter (Book A, P.282 No.279) found mound with 2 pits plain and fence post in middle of mound. 1/16 East set stake M & L 19.92 1/2 (chains). 1/16 South set stake M & L 20.04 1/2 (chains). 1/16 center NE 1/4 set stake M & L on N-S 1/16 line 20.07 (chains).

9-1876 T. Hunter (Book A, P.304 No.299) found corner.

5-1896 T. Hunter (Book A, P.598 No.543) corner missing, could not be seen. Meas South line 29 found 1/16 East of corner by using porp meas as in former surveys listed and projecting ones remains 1/16 stake East found on digging remains of old post hole and post of rotted post. Set boulder 8 x 9 x 16 in its place. 1/16 West set stake and stone M & L 19.96 (chains). 1/16 East set boulder 5 8 x 9 x 14 M & L 19.91 1/2 (chains) in remains of old stake set (P.282). 1/16 North set stone 6 x 10 x 15 with stake by side M & L 19.90 1/2 (chains). 1/16 center SE 1/4 29 set stake M & L N-S 1/16 line.

7-30-1971 County Surveyor dug on East side corner post as it leaned West, fences N-S-W found many stones deep some of them. One vertical near twp 18" NE of corner post about size of corner but little too big and no stake. Set 1 1/4 x 3' pipe at base of completely rotted corner post on NE side in rotted base. In future entire area 3' around corner post should be clay and all small and wrong sized stones removed before setting a final corner. Ran and meas line North, shot very close due to tall cornfields 300' + to offset 36' West. Dug and probed in very dence plum hag in line straight fence East but found no vertical stones of proper size. Fence running East almost exact record from corner as set 1313.63' but only 1309.72 North to E-W 1/4 line fence. Set 1/16 until proven otherwise 1 1/4 x 3' pipe with holes in sides at above meas and on best line able to run between pipe set at 1/4 29-32 and corner post at center 29.

12-23-1971 County Surveyor meas carefully West from 28-29-32-33 a nail set 7-29-1971. Dug extensively at 1/16 West at fence corner found massive "dead man" stone W-N-S which evidently destroyed record corner found bottom old corner post at 1315.4 (R1314.4). Cont meas only West to pipe set.

11-6-1973 County Surveyor found 1/16 stone West set 5-1896 Hunter P.598 at M & L 1317.36 at very near record rough meas from West stone down 15 inches + about .85 S of fence 2.0 ESE wood post.

3-4-2010 County survey crew found 1 1/4" pipe down 0.4' in good condition.

10-22-2012 County survey crew found 1 1/4" pipe in good condition. Set 4' telspar pipe with cast iron cap over the found pipe.