Certificate of Location of Government Corner

ID#: 552905 **Description:** SEC COR 29 30 31 32 55 **Date Set:** 8/6/1965 **County:** Olmsted

Section: 29 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' west of centerline of N-S twp road and in line with fence west
Electric fence post 1.0' above ground in fence W 100.0'
This corner is located by GPS measurement

Corner History:

5-1854 Gov't Notes Michael Karrick 80.00 set post for corner to sections 29,30,31 and 32. Erected mound with trench, pits, charred stake and Osage Orange seeds at each angle.

6-7-1875 T. Hunter (P.282 No.279) used stake standing in mound to set 1/4 cor 31-32 M & L no meas given.

6-11-1875 T. Hunter (P.284 No.281) found mound and pits with stake at corner of field. 1/16 South set marked stake M & L 19.96 (1317.36). 1/16 center NE 1/4 31 set marked stake M & L 19.92 on EW 1/16 line (1314.72).

9-1876 T. Hunter (P.304 No.299) found stake in mound at corner of fence (P.284). 1/16 East set marked stake M & L 19.96 1/2 1317.69. 1/16 North set marked stake M & L 19.99 1319.34.

5-1896 T. Hunter (P.598 No.543) corner gone projected line from NW 29 over W 1/4 29 South double dist or 39.96 1/2, drove stake on North side big boulder stone in trench. 1/16 East set stone and stake M & L 19.96 1317.36. 1/16 North set temp stake M & L 19.98 1318.68. 1/16 center SW 1/4 29 set stake and stone at inters lines.

6-1923 J. Kerr (P.392B BK.8 P.11) found Frasers stake drove iron stake thru remains of old stake and piled rock around it. Meas South 2633.95 M & L.

8-6-1965 County Surveyor found 3/4" rod driven thru old stake with boulder by side. Set CIM over 1/2"x2' rod and boulder.

11-6-1973 County Surveyor did not locate corner only with dip needle. Meas East with 300' tape about 8' North of fence which in not in good shape. Found lone wood post nearly rotted off with ?? from both East and West anchored to it. Fence row at corner area filled with boulders some too large to move. On digging area shows at least 12 to 15 inches erosion by wind etc. all stones loose as when thrown into fence iron finally located vertical peach seed shaped boulder very pointed and vertical in clean original soil with wide sized edges N & S examined closely for remains of stake but found none raised stone nearer to surface with 40d nail and piece of chain link below as no iron at hand. Corner .85 S of woven wires 2.0 ESE of wood post dug out all rocks in area and piled up to East of corner. Line and meas can now check 1/4 29-32 as set.

5-5-2009 County Surveyor found CIM down 0.5' in good condition.