Certificate of Location of Government Corner

ID#: 552906 **Description:** 1/4 SEC COR 29 30 55 **Date Set:** 8/9/1965 **County:** Olmsted

Section: 29 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 3' west of centerline of N-S twp road and 4 1/2' south of fences east and west
County highway disk in PP SE 88.1'
This corner is located by GPS measurement

Corner History:

5-1854 Michael Karrick 40.00 set quarter section post in mound with trench, pits, charred stake and Osage Orange seeds NE and SW.

9-1875 T. Hunter (P.304 No.299) corner missing and could not be found, set marked stake M & L 39.98 N 5' W no knowledge of corner by settlers. 1/16 South set marked stake M&L 19.99 to stake in mound (1319.34). 1/16 East set marked stake M&L 19.97 1/2 to stake set at center (1318.35)

5-1896 T. Hunter (P.598 No.543) found stone as corner with stake driven (P.304) underneath drove new stake set stone on top of stake as found. 1/16 South set temp stake M&L 19.98 (1318.68) S 1/2° W. 1/16 East set stone with stake by side M&L 19.97 1/2 (1318.35) to stake set N 88 3/4 W. Meas North 39.96 1/2 (2637.7) to stake and stone set P.304

8-9-1965 J. Kerr found boulder with stake below. Drove new stake, set stone on top of stake. Set CIM at stone and stake location.

12-9-1971 County Surveyor only 1 RP left, meas East recorded 1318.35 found 7 x 8 x 14± boulder with definate sound wood stake underneath over 2' North of E-W fence at about 1315± (very cold, did not continue line) must find 1/4 29-30 CIM and rerun and re meas line E.

5-5-2009 County Surveyor found CIM down 0.7' in good condition.