Certificate of Location of Government Corner

ID#: 552909 **Description:** SEC CEN 29 55 **Date Set:** **County:** Olmsted

Section: 29 **Township:** 105N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

9-12-1876 T. Hunter (P.304 No.299) set stake at inters lines from 1/4 cor. 1/16 West set stake M&L 19.97 1/2 (1318.35) to stake at W 1/4 cor set M&L bearing North N 2' W bearing East N 89° 20 W.

5-13-1896 T. Hunter (P.598 No.543) set oak stake flush with surface at true inters lines. 1/16 West set stone with stake by side M&L 19.97 1/2 (1318.35) N 88° 3/4 W. 1/16 South set stone 6 x 10 x 15 with stake by side M&L 19.90 1/2. 1/16 center SW 1/4 29 set stake and stone inters lines N 1/2° E. Set stakes for fenceing N-E & S from above corner. 1/16 East set burr oak stake M&L 19.93 N 88 3/4° W. 1/16 center SE 1/4 29 set stake M&L on N-S 1/16 line.

7-30-1971 County Surveyor ran and meas from corner post at 1/4 29-32 North. Searched for 6 x 10 x 15 stone at 1/16 set M&L 19.90 1/2 (1313.73) which seemed to line main fence East (very brushy) finally set 1 1/4" x 30" pipe as 1/16 on line of corner posts at center 29 and 1/4 29-32 at 1313.63 supposed M&L but meas North to fence E-W only 1309.72 indicating center oak stake could be North of fence line.

12-9-1971 County Surveyor meas from 1 RP remaining and magnetic dip of 1/4 29-30 with random transit line to fence line near center 29 (not definate) and easily found 1/16 stone West of center 29. Boulder 7 x 8 x 14 ± 2' North of fence line E & W, also found wood stake below (underneath) stone found. Chainage from West seemed short of 1318.35 by at least 3' or more (very cold and lots of snow).