Certificate of Location of Government Corner

ID#: 553004 **Description:** 1/4 SEC COR 30 31 55 **Date Set:** 8/10/1965 **County:** Olmsted

Section: 30 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1 1/2' east of centerline of CR 149
County highway disk in CP W 31.62' (low)
This corner is located by GPS measurement

Corner History:

5-1854 Gov't notes Michael Karrick 39.60 set quarter section post in mound with trench, pits, charred stake and Osage Orange seeds NE and SW.

6-1875 T. Hunter (P.284 No.281) found mound and pits with stake hole in center but no stake. 1/16 West set stake as corner. Actual meas 40.14 R39.60 setting corner at 2027 then 19.87 to NW corner 30 N 89° 20 E. 1/16 South set stake M&L 20.01 1/4 N 3/4° W. 1/16 center NW 1/4 31 set stake inters lines. 1/16 center NE 1/4 31 set stake M&L 19.92 on E-W 1/16 line.

6-1898 W. Fraser (P.635 No.573) corner set by Hunter gone or reset. Run line from S 1/4 31 over center 31 and replaced corner with stone 3 x 12x 14 with stake. This meas is shorter by 2 links than Hunters by proved correct by 1/16 corner. 1/16 South set stone and stake M&L 20.00 1/4 couldn't find Hunters stake. 1/16 West set stone and stake line and porp meas 2019 then 1979. 1/16 East set small stake M&L 19.89. 1/16 center NE 1/4 31 found Hunters stake set new stake and stone M&L on EW 1/16 line 19.90 1/2 1313.7'. 1/16 center NW 1/4 31 set stake and stone inters lines stake on East edge big boulder stone.

8-10-1965 J. Kerr found stone as recorded with iron stake on west side. Set CIM above stone.

5-1-1980 county highway department (book 477 Pg 6) found CIM in good condition. Took ties.

9-24-1992 County Surveyor at 1/16th West of 1/4 corner 30-31 dug for stone and stake set by W. Fraser in 1898. Found stone 1 1/2" x 8" x 10" beside post stub circled by huge boulder stones on low side of silted in fence row the post stub was axe sharpened and 3 1/2' long. The stone was on South side of post 3' North of filtered in woven wire fence running E-W.

5-5-2009 County Surveyor found CIM down 1' in good condition.