Certificate of Location of Government Corner

ID#: 553206 **Description:** 1/4 SEC COR 31 32 55 **Date Set:** 6/3/2011 **County:** Olmsted

Section: 32 **Township:** 105N **Range:** 15W **Monument Description:** Cast iron cap on telspar pipe

Reference Ties:

The corner falls 7' north of centerline of CR 108 and 3' east of centerline of twp road north
PK nail in PP #6238 NE 34.66'
PK nail in S end 24" CMP SW 66.02'
Punch mark in N end 24" CMP NW 63.59'
This corner is located by GPS reference stations "Ernest A & B"

Corner History:

5-1854 Michael Karrick 12.50 creek 15 lks wide runs East. 40.00 set quarter section post in mound with trench, pitts, charred stake and Osage Orange seeds NE and SW.

6-1875 T. Hunter (P.282 No.299) could find no evidence or knowledge of corner. Set corner M&L (no meas) from stakes standing and preserved.

6-1875 T. Hunter (P.284 No.281) All evidence destroyed in opening and working of road, land marshy set stake M&L 39.92 2634.72. 1/16 corners North and South set M&L 19.96 1317.36 N 1° W. 1/16 West set stake M&L 19.95 1316.7 S 88° 36' W. 1/16 center NE 1/4 31 set stake M&L 19.92 on E-W 1/16 line.

6-1898 W. Fraser (P.635 No.573) drove nail in plank? M&L 39.90 for use this survey. 1/16 South set stake and boulder M&L 19.95 1316.7. 1/16 West found Hunters stake M&L 19.92 1/2 1315.05 set stake and stone. 1/16 North found Hunters stake M&L 19.95 1316.7 set new stake. 1/16 center NE 1/4 31 found Hunters stake set new stake and stone. 1/16 center SE 1/4 31 set stake M&L 19.94 1316.04 on EW 1/16 line.

6-1923 J. Kerr (P.392B book 8 page 11) set iron pipe M&L 2633.95 (R39.90 2633.4)

10-1923 County Highway Department Book 39 P.6 E-W 1/4 line S.32 R Dell, found 1" iron pipe. RP's fence post South 300'. F.P. NW 26.1 F.P. NE 29.1 Meas East 5263.6.

7-28-1971 County Surveyor set nail in center road North at 2634.0 in line fence running South. R. Hunter 2635.38 W. Fraser 2633.4 J. Kerr 2633.95. Corner finally found at 2632.8. Run random line and meas West.

8-16-1971 County Surveyor dug for corner, found 1" x 24" pipe set by J. Kerr 1.2' North 2.5' East of nail set. Meas West to 1/16 stone found 131`3.6 (R1315.05). 1/16 found .5' N of line run. Meas West to center stone found 1315.32 (R1315.05) which was found .9' S of line run. Set iron rod as temp corner. Dug further for previous corners recorded, found nothing. Iron set as temp corner. 3' E center road North. 7' N center roads East and West. No RP's set only to original nail 37.43 NE to ground wire of PP #6238 61.75 W to + on N end 24" galv culvert.

2-28-1990 Vince Fangman found 7/8" pipe down 1'. Set 1/2" pipe w/cap 14888 over the 7/8" pipe. Measured the following reference points: P.K. in PP #6238 NE 34.66'. P.K. in S end of 24" culvert SW 66.02'. + in N. End 24" culvert NW 63.59'.

3-19-2009 County Surveyor found 1/2" pipe down 0.5' and leaning. Dug down to bottom of 1/2" pipe and found it was drove into a 1" pipe that was also leaning west. Removed both pipes.

10-20-2010 County Surveyor Department computed location using reference ties set by Vince Fangman in 1990.

6-3-2011 County survey crew set 4' telspar pipe with cast iron cap at the 2010 computed location.