Certificate of Location of Government Corner

ID#: 553305 **Description:** S SEC COR 32 33 55 **Date Set:** 11/19/1993 **County:** Olmsted

Section: 33 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls in line with fence west and 4' north of fence SE-NW
County Survey Disk in brace post SW 3.25'
Post w/sign 1' north
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes 80.00 set post for corner to sec 32 & 33, built mound with trench per instruction. Drove charred stake in center and planted Apple tree seed in NW corner. Elm 20 N 26° E 169 lks.

6-1875 T. Hunter (P.282 No.279) found original stake in clump of willows avered as to where it always stood, although 70 lks short West to S 1/4 32 and way out of line going North. 1/16 West set stake flush with ground surface M&L 19.65. Meas North 40.06 N 10' E then 40.06 N 1° W to NE 32.

6-1877 T. Hunter (P.319 No.313) used established corner at SW 33 to meas East 2 miles to SE corner 34 160.53 chs.

6-1878 T. Hunter (P.351 No.343) found original stake as described P.282 as "L". Meas West to S 1/4 32 as M (orig stake) 39.41.

7-1893 W. Fraser (P.521 No.487) found stake P.282, set stone boulder 6 x 6 x 18 in place of stake. West 4.71 1/2 (311.2) to N 1/4 4 104-15 called "M" found stake set stone boulder 6 x 8 x 16. 1/16 East set boulder stone M&L 20.03 to NE corner 4 a stone. Also road layout.

6-1923 J.Kerr (P.392B) found stone as described by Fraser. Meas North 2644 to corner also 2644 North to sec corner.

1935 County Highway Department B.79, found nothing set stake M&L on twsp line between 1/4 corner.

11-16-1993 County Surveyor dug for W.F. stone set at TH stake location using W.F. 4.71 1/2 chs.from 1/4 line in section 4 104-15 We dug to cover full measure from 1/4 corner 32-33 by TH and North 6' using line from East. Dug 1' West & 3' East of T.N. clay was 1' deep. This area is 15' below bank of river at flood line. We found nothing.

11-18-1993 County Surveyor, after finding N 1/4 4 104-15 we dug again North of previous digging found W. Fraser 6 x 6 x 18 stone with stake on East side 1.8' deep to top of stone. The stone is in line with fence West and is 4' North of diag. Fence running SE-NW. Set post and sign on North side.

11-18-1993 County Surveyor 1/16 west of S 32-33, dug for T. Hunter stake. We dug from 1' West to 3' East of T.N. in line of fence North and 1' South of angle iron CP in concrete to fence E-W-N. We found a post stub leaning Swly from stones piled around it. 1' East and .5' North of T.N. we found a soft dark spot running down ± 18" this maybe Hunters stake location it falls SE of post stub. This spot is 1.9' East and .3' S of T.N.

11-19-1993 County Surveyor set cast iron cap on telspar pipe at W. Fraser stone location. Placed stone on North side of monument. CSD in brace post SW 3.25'. Sign and post 1' North.

3-4-2010 County Surveyor found cast iron cap on telspar pipe at surface in good condition.