Certificate of Location of Government Corner

ID#: 553404 **Description:** S 1/4 SEC COR 34 55 **Date Set:** 11/10/2011 **County:** Olmsted

Section: 34 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Cap on Telspar Pipe

Reference Ties:

The monument is at the surface
The corner falls 3' south of powerpole line
Post with sign, North, 2'
This corner is located by GPS measurement

Corner History:

9-1853 40.00 set gr sec post built mound with trench per instruction. Drove charred stake in center and planted Apple tree seed in NW corner. 61.40 creek 50 lks wide runs NE

6-1877 T. Hunter (P.319 No.313) corner gone also all corner between NW cor stone of sec. 3 and SE cor 34 (a stake in mound). Meas from SE 34 105-15 to SW cor S.33 105-15. 160.53 chs overrunning 53 links. Set stake for S 1/4 34 40.13 West of SE 34, which comes 5.00 chs East of stone and stake 3 x 10 x 15 boulder. Set this survey as NE cor. Sec. 3.

5-22-1979 County Surveyor, (1979 Bk pages 63,87) Set a nail 3' South of the end post of the fence running North and in line with the fence East. Dug and found base of old post 1.2 N and .2 West of the nail. Dug at a point 5 chains East of N 1-2 (found) and on line to the corners found at N 1/4 cor. 2 and S 34-35 for 1 1/2' N, 1 1/2' S, 2' W and 2' E. Found three boulders and wire loop but could not find stake or post location.

12-16-2002 Olmsted County Surveyor computed a coordinate location for this corner with the preparation of Olmsted County Right of Way Plat No. 138 (although the actual corner is not graphically shown on the plat). It was computed on a line from the northwest corner of section 2-104-15 to the north quarter corner of section 2-104-15 and at an original government survey measurement of 5 chains (330.00') from the northwest section corner of 2-104-15.

11-10-2011 County survey crew set a 4' telspar pipe with cast iron cap using the 2002 computed coordinates.