Certificate of Location of Government Corner

ID#: 553504 **Description:** S 1/4 SEC COR 35 55 **Date Set:** 6/8/1979 **County:** Olmsted

Section: 35 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1/2' south of E-W fence and 140' west of west bank of river
County Survey Disk in E side blazed 14" Ash NNW 101.18'
County Survey Disk in NW side blazed 7" Elm NE 68.08'
County Survey Disk in S side blazed 15" Ash WNW 46.38'
Post w/sign 1' WSW
This corner is located by GPS reference stations "Higgins A & B"

Corner History:

9-1853 Gov't Notes Elisha Norris, Deputy Surveyor West on South boundary of Section 35. 40.00 chs. Set quarter section post. Elm 14 in. N84°W 235 lks. Elm 16 in. N17°E 238 lks.

6-23-1877 T. Hunter (Book A, Page 320, No. 314) (Field Book 5, Page 20) shows S 1/4 35-105-14 to be 4.90 chains east of north corner Sec. 1-2 104-15

6-7-1878 Thomas Hunter, County Surveyor (Old Field Book 5, Page 75) states: "1/4 post missing".

6-8-1979 County Surveyor at Gov't measure from N. Sec. Cor. 1-2 (See Cerificate filed on this corner). In sand subsoil we found a 3" diameter hole of charred wood. We shaved down the side and the charred wood extended down another 1' and tappered to a point. Set a C.I.M. over a 3/4"x3' iron driven in the stake mark as the corner.

11-2-2000 County survey crew found CIM down 0.2' in good condition.