Certificate of Location of Government Corner

ID#: 553505 **Description:** S SEC COR 34 35 55 **Date Set:** 5/23/1979 **County:** Olmsted

Section: 35 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 2 1/2' north of fence east and in line with the centerline of CR 115 north
County Survey Disk in NW side PP #24836 NE 67.71'
County Survey Disk in S side CP E 26.85'
County Survey Disk in S side 15" Burr Oak ESE 38.15'
Post w/sign 1 1/2' SE
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes Elisha Norris, Deputy Surveyor West on the South boundary of Section 35. 80.00 chs. Set post for corner to sections 34 and 35 Built mound with trench per instruction. Drove charred stake in center and planted apple seed in N.W. corner.

6-23-1877 Thomas Hunter, County Surveyor, (Book A, Page 320, No. 314 and Old Field Book 5, Page 20) found corner standing in mound. He set the N. 1/4 Cor. 2 on line from this corner to N.W. Cor. 2 and midway between the N.E. Cor. 2 and the N.W. Cor. 2 which point came 5.07 1/4 chains west of S. Sec. Cor. 34-35.

6-15-1895 William Fraser, County Surveyor, (Book A, Page 637, No. 574 and Old Field Book 9, Page 11-16) found stake in mound.

5-23-1979 County Surveyor measured 5.07 1/4 Chains east from N. 1/4 Cor. 2 (found) as in Hunter's survey and dug for S. Sec. Cor. 34-35. Found a 1/2" square iron with 4 or 5 boulders around it and driven into a black mark which extended well into clay. Set a square pipe (telspar) with Cast Iron Cap over the iron found.

11-2-2000 County survey crew found cast iron cap on telspar pipe down 0.1' in good condition.