Certificate of Location of Government Corner

ID#: 553604 **Description:** S 1/4 SEC COR 36 55 **Date Set:** 6/29/1971 **County:** Olmsted

Section: 36 **Township:** 105N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' north of centerline of E-W twp road
Number plate in PP #6030 WNW 161.37'
40d nail in E side 12" Ash N 45.3'
16d nail in E side 6" Elm ENE 48.68'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes: 40.00 set quarter section post. White Walnut 10 N 26° E 20 lks. Black Oak 10 N 20° W 36 lks.

6-1878 T. Hunter (Page 348 No.341) corner lays 4.50 chs East of NW cor. sec. 6 297' a stake standing testing culvert by 2 bearing tree stumps still marked plainly. Left stake as found 6.92 + 18.88 + 18.78-4.50=39.88. Meas East to twsp corner 2632.08 much difficulty at NE cor 6

1895 W. Fraser (Book A, Pg. 574, No. 525) found the stake and set a new stake, iron, and stone. He also drove an iron stake to the east midway and on line at 1316.04'

4-28-1906 C. Armstrong (P.106B) used corner as set by P.574. Found iron stake as 1/16 East no meas. 1/16 North set stone 20.10 M&L wouldn't hurt to check survey in court house, writing of record near illegable.

6-8-1971 County Surveyor measured SW 31 105-14 (twsp cor) West, set nail at 2632.0 in center road.

6-22-1971 County Surveyor dug with tractor, found stone, wood stake and iron bar. Used wood stake as corner as recorded. Set CIM over corner as found 6-29-1971. Corner not on direct line of SW 31 105-14 and NW 104-14. S 1/4 36 lies South 1.13' of direct line above corners. 1/16 iron East found lies .25' North of direct line of S 1/4 36 105-15 and SE 36 105-15 or .31' South of line between SE 36 105-15 and NW 6 104-14. Meas West to twsp corner NW 6 104-14 295.3 R 297.0. Meas East to 1/16 iron found 1316.23 R 1316.04 then East to twsp cor SE 36 1315.55

11-8-1971 County Surveyor measured and ran line North found recorded 1/16 boulder with cross set by C. Armstrong 4-1906 P.106B at 1329.0 R1326.6 set 4" boiler flue up 6' in S side stone as found. Cont line North set point on proj line on S bank river at 1312

10-31-2000 County survey crew found CIM down 0.6' in good condition.