# Certificate of Location of Government Corner

**ID#:** 553609 **Description:** SEC CEN 36 55 **Date Set:** **County:** Olmsted

**Section:** 36 **Township:** 105N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

**Reference Ties:**

**Corner History:**

4-1906 C. Armstrong (P.106B S.36) corner falls in river 10" white oak SW 25 links. 8" elm SE 26 links trees unmarked. 1/16 East (corner 2) platted as boulder stone with cross on top, set M&L 19.925 (1315.0). 1/16 South (corner 3) platted as boulder stone with cross on top, set M&L 20.10 (figures blurred see court house) 1326.6

11-8-1971 County Surveyor projected line from 20' offset West at S 1/4 36 (CIM over stone) and 20' offset West of cross on boulder at 1/16 stone North 1329.0 1326.6. Set 40d nail on corrected line on river bank at 1312.0 North of 1/16 stone some 5' ± South of river bank. Set steel fence post with flat steel 3" x 10" ± welded to top of post driven half length in bank. Also set 40d on true line at 1000' North of stone. This came 3' East S end large rotted log laying N & S. Also projected 20' offset line North to 1/4 25-36.

11-15-1995 McGhie & Betts used computed center.

8-19-1998 V. Fangman used computed center at intersecting quarter lines.