Certificate of Location of Government Corner

ID#: 601805 **Description:** W SEC COR 18 19 60 **Date Set:** 12/14/1999 **County:** Winona

Section: 18 **Township:** 106N **Range:** 10W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 32' SW of centerline of twp road on curve, 33' north of main line of E-W fence and 27' east of N-S fence
This corner is located by GPS reference stations "FMK & Kaehler"

Corner History:

1853 Gov't Notes: N. 80.00 chains set post corner and dug trench. B.T.'s Burr Oak 12" N65°E 86 links. Burr Oak 8" N3°W 112 links.

7-1890 Thos Fraser (P.444 No.429 S.12 and co. line) C.Carter and others found stone 4x6x10 set by Donahue when original stake was in place in mound. Found by using stump of NE B.T.

4-28-1942 J. Kerr Winona Co. Book #1 P.24 found limestone and stake at this point several feet west of the stake as set by E.C.Burns. Drove iron pipe through remains of wood stake in replacing it. 60d sp in 3' maple SE 46.0', 60d sp in 30" maple E of NE 88.0'. Meas north 5301.6 to corner.

1-7-1972 County Surveyor found large iron pipe set by J. Kerr. Corner lies in slope of curve at corner of Twsp road on S side. 45.15' SE to 30d driven over head of original RP nearly grown over in NE'ly side of huge maple up 18" 87.7' ENE to 30d on SE side 2nd maple 30" + near root. 51.9' NW to 30d nail on NE side 24" ± maple in large root running NE'ly above ground. Meas south on 64' west and random S. Found 1/16 fence E-W at 1313.5', found random line from east set by McGhie 2664.75. Con't line and meas south total 5269.05 98.5' W of stone.

8-14-1987 County Surveyor found cast iron monument down 2' in good condition.

12-14-1999 County Surveyor found CIM 16" deep in field drive. Set CIM 15" long over CIM.

4-5-2000 County Surveyor found cast iron monument down 0.3' in good condition.